

# Package: dsrTest (via r-universe)

September 15, 2024

**Type** Package

**Title** Tests and Confidence Intervals on Directly Standardized Rates  
for Several Methods

**Version** 1.0.0

**Date** 2022-06-12

**Author** Michael Nelson

**Maintainer** Michael Nelson <michael.nelson.r.pkg@gmail.com>

**Description** Perform a test of a simple null hypothesis about a  
directly standardized rate and obtain the matching confidence  
interval using a choice of methods.

**Encoding** UTF-8

**License** GPL (>= 2)

**RoxygenNote** 7.2.0

**Roxygen** list(markdown = TRUE)

**Depends** R (>= 2.10)

**Imports** stats, exactci, asht (>= 0.9.1), loglognorm,

**Suggests** testthat, knitr, rmarkdown, covr

**URL** <https://github.com/mnelsonr/dsrTest>

**BugReports** <https://github.com/mnelsonr/dsrTest/issues>

**VignetteBuilder** knitr

**LazyData** true

**Repository** <https://mnelsonr.r-universe.dev>

**RemoteUrl** <https://github.com/mnelsonr/dsrtest>

**RemoteRef** HEAD

**RemoteSha** 55f4b8ccdff179c2db7f22b5f2582cbba6742f66

## Contents

dSrTest-package . . . . .	2
asymptoticControl . . . . .	3
betaControl . . . . .	4
dobsonControl . . . . .	5
downs.mi . . . . .	5
dSrTest . . . . .	6
gammaControl . . . . .	8

<b>Index</b>	<b>10</b>
--------------	-----------

---

dSrTest-package	<i>Tests and Confidence Intervals on Directly Standardized Rates for Several Methods</i>
-----------------	--

---

### Description

Perform a test of a simple null hypothesis about a directly standardized rate and obtain the matching confidence interval using a choice of methods.

### Details

The DESCRIPTION file: This package was not yet installed at build time.

Index: This package was not yet installed at build time.

The function `dSrTest()` implements a number of different parameterizations and methods for computing confidence intervals on directly standardized rates. These methods are described in detail in Fay and Feuer (1997), Tiwari et al (2006), Ng et al (2008) and Fay and Kim (2017).

The various `<method>Control()` functions allow modifications to the general approaches.

### Author(s)

Michael Nelson

Maintainer: Michael Nelson <michael.nelson.r.pkg@gmail.com>

### References

Dobson, AJ, Kuulasmaa, K, Eberle, E and Scherer, J (1991) 'Confidence intervals for weighted sums of Poisson parameters', *Statistics in Medicine*, **10**: 457–462. doi:10.1002/sim.4780100317

Swift, MB (1995) 'Simple confidence intervals for standardized rates based on the approximate bootstrap method', *Statistics in Medicine*, **14**, 1875–1888. doi:10.1002/sim.4780141704.

Fay MP & Feuer EJ (1997) 'Confidence intervals for directly standardized rates: a method based on the gamma distribution.' *Statistics in Medicine*. **16**: 791–801. doi:10.1002/(sici)10970258(19970415)16:7<791::aid-sim500>3.0.co;2#

Tiwari RC, Clegg LX, & Zou Z (2006) 'Efficient interval estimation for age-adjusted cancer rates.' *Statistical Methods in Medical Research* **15**: 547–569. doi:10.1177/0962280206070621

Ng HKT, Filardo, G & Zheng G (2008) 'Confidence interval estimating procedures for standardized incidence rates.' *Computational Statistics and Data Analysis* **52**: 3501–3516. doi:10.1016/j.csda.2007.11.004

Fay, MP & Kim S (2017) 'Confidence intervals for directly standardized rates using mid-p gamma intervals.' *Biometrical Journal* **59**(2): 377–387. doi:10.1002/bimj.201600111

## See Also

[wspoissonTest](#)

## Examples

```
## using the example from asht::wspoissonTest
## birth data on Down's syndrome from Michigan, 1950-1964
## see Table II of Fay and Feuer (1997)
## xfive = counts for mothers who have had 5 or more children
## nfive and ntotal are number of live births
xfive<-c(0, 8, 63, 112, 262, 295)
nfive<-c(327, 30666, 123419, 149919, 104088, 34392)
ntotal<-c(319933, 931318, 786511, 488235, 237863, 61313)
## use mult =10^5 to give rates per 100,000
## gamma method of Fay and Feuer (1997) is default
dsrTest(xfive, nfive, ntotal, method = "gamma", mult = 1e5)
## Dobson et al (1991)
dsrTest(xfive, nfive, ntotal, method = "dobson", mult = 1e5)
## Asymptotic with log transformation
dsrTest(xfive, nfive, ntotal, method = "asymptotic", mult = 1e5,
control = list(trans = "log"))
```

---

asymptoticControl

*Control Function for Asymptotic Method Confidence Intervals*

---

## Description

Specify the transformation to apply to the distribution of the MLE.

## Usage

```
asymptoticControl(trans = c("none", "log", "loglog", "logit"), ...)
```

## Arguments

trans	Transformation apply to the MLE distribution.
...	Currently ignored.

**Value**

A list with values

trans

---

betaControl

*Control Function for Beta Method for Confidence Intervals*

---

**Description**

Modification to the Beta method. The options are "none" or the same modifications as applied to the Gamma Method (see [gammaControl](#)) are implemented. wmtpe="none" and wmtpe="tcz" have been investigated by Tiwari et al (2006) and Ng et al (2008).

**Usage**

```
betaControl(wmtype = c("none", "tcz", "max", "mean", "minmaxavg"), ...)
```

**Arguments**

wmtype	character type of modification to the Beta Confidence Interval
...	Currently ignored.

**Value**

a list with values

wmtype	modification to Beta Confidence Interval to implement
--------	---

**References**

Tiwari RC, Clegg LX, & Zou Z (2006). 'Efficient interval estimation for age-adjusted cancer rates.' *Statistical Methods in Medical Research* **15**: 547–569. doi:10.1177/0962280206070621

Ng HKT, Filardo, G & Zheng G (2008). 'Confidence interval estimating procedures for standardized incidence rates.' *Computational Statistics and Data Analysis* **52** 3501–3516. doi:10.1016/j.csda.2007.11.004

---

dobsonControl	<i>Control Function for Dobson Method Confidence Intervals</i>
---------------	--

---

**Description**

Provides a list of arguments to pass to [poisson.exact](#).

**Usage**

```
dobsonControl(midp = FALSE, tsmethod = c("central", "minlike", "blaker"), ...)
```

**Arguments**

midp	logical, use mid-p values? Currently only permitted where tsmethod = "central".
tsmethod	character giving two-sided method
...	Currently ignored..

**Value**

a list with values

midp

tsmethod

**See Also**

[poisson.exact](#)

---

downs.mi	<i>Downs' syndrome cases and of total live births by maternal age and birth order, Michigan, 1950-1964.</i>
----------	---

---

**Description**

This data reproduces table 14.4 in Fleiss (1981) and which is drawn from a large-scale study in Michigan 1950-1964 of the effect of Maternal age and Birth order on Down Syndrome and Leukemia (Stark and Mantell, 1966).

**Usage**

```
downs.mi
```

**Format**

This data.frame contains the following columns:

Age The age category of the mothers.

BirthOrder The birth order.

Cases The number of cases of Down's Syndrome.

Births The number of live births.

Standard A "standard" population, derived as the total number of births in each age category

**Source**

The data were obtained from table 14.4 (p 249) in

Fleiss, JL (1981) *Statistical Methods for Rates and Proportions*, Wiley, New York.

The original study is

Stark CR and Mantel N (1966) 'Effects of maternal age and birth order on the risk of mongolism and leukemia' *J Natl Cancer Inst* **37** (5) 687–698. doi:10.1093/jnci/37.5.687

---

dsrTest

*Tests and Confidence Intervals on Directly Standardized Rates*

---

**Description**

A number of methods have been proposed for calculating confidence intervals for directly standardized rates. Ng et al (2008), compare a number of methods, some of which are implemented here. The default uses the Gamma method by Fay and Feuer (1997) and implemented in [wspoissonTest](#).

**Usage**

```
dsrTest(
  x,
  n,
  w,
  null.value = NULL,
  alternative = c("two.sided", "less", "greater"),
  conf.level = 0.95,
  mult = 1,
  method = c("gamma", "asymptotic", "dobson", "beta", "bootstrap"),
  control = list()
)
```

**Arguments**

<code>x</code>	a vector of strata-specific counts.
<code>n</code>	a vector of strata-specific time bases for counts.
<code>w</code>	a vector of strata-specific weights (or standard populations).
<code>null.value</code>	a null hypothesis value of the directly rate, if NULL no test is done. If not NULL, provide in rate per mult.
<code>alternative</code>	type of alternative hypothesis.
<code>conf.level</code>	confidence level for the returned confidence interval.
<code>mult</code>	a factor to multiply the estimate and confidence intervals by, to give rates per mult.
<code>method</code>	Method used to perform the test and construct the confidence interval. See details.
<code>control</code>	list of arguments / type of modification used for each method. See details and relevant "xxxxControl" documentation

**Details**

Five classes of method have been implemented here:

"gamma" Calls [wspoissonTest](#). By default uses the Gamma Method proposed by Fay and Feuer (1997). Modifications proposed by Tiwari et al (2006) and Fay and Kim (2017) also implemented - see [gammaControl](#).

"asymptotic" Using the normal approximation of the MLE or transformed MLE distribution - see [asymptoticControl](#)

"dobson" Uses the method proposed by Dobson et al (1991). Estimating the confidence interval on the unweighted sum is done by calling [poisson.exact](#) - both the exact method and a mid-p method are possible - see [dobsonControl](#).

"beta" Methods based on the beta distribution by Tiwari et al (2006) - see [betaControl](#).

"bootstrap" Approximate Bootstrap method by Swift (1995). P-values are estimated by solving for p.

For each method there is a `control` function that will return a list of parameters that can be used to define sub-types of each of the broad groups

**Value**

a list with class "htest" containing the following components:

<code>statistic</code>	number of strata or summands: $k = \text{length}(x)$
<code>parameter</code>	mult
<code>p.value</code>	p-value, set to NA if <code>null.value = NULL</code>
<code>conf.int</code>	confidence interval on the true directly standardized rate
<code>estimate</code>	directly standardized rate
<code>null.value</code>	null hypothesis value for the DSR

alternative	alternative hypothesis type
method	description of the method
data.name	description of the data

## References

- Dobson, AJ, Kuulasmaa, K, Eberle, E and Scherer, J (1991) 'Confidence intervals for weighted sums of Poisson parameters', *Statistics in Medicine*, **10**: 457–462. doi:10.1002/sim.4780100317
- Swift, MB (1995). 'Simple confidence intervals for standardized rates based on the approximate bootstrap method', *Statistics in Medicine*, **14**, 1875–1888. doi:10.1002/sim.4780141704.
- Fay MP & Feuer EJ (1997). 'Confidence intervals for directly standardized rates: a method based on the gamma distribution. *Statistics in Medicine*\*. **16**: 791–801. doi:10.1002/(sici)10970258(19970415)16:7<791::aid-sim500>3.0.co;2#
- Tiwari RC, Clegg LX, & Zou Z (2006). 'Efficient interval estimation for age-adjusted cancer rates.' *Statistical Methods in Medical Research* **15**: 547–569. doi:10.1177/0962280206070621
- Ng HKT, Filardo, G & Zheng G (2008). 'Confidence interval estimating procedures for standardized incidence rates.' *Computational Statistics and Data Analysis* **52** 3501–3516. doi:10.1016/j.csda.2007.11.004

## See Also

[wspoissonTest](#), [poisson.exact](#), [gammaControl](#), [dobsonControl](#), [asymptoticControl](#), [betaControl](#)

---

gammaControl

*Control Function for Gamma Method Confidence Intervals*

---

## Description

Provides a list of arguments to pass to [wspoissonTest](#).

## Usage

```
gammaControl(
  midp = FALSE,
  nmc = 0,
  wmtype = c("max", "mean", "minmaxavg", "tcz"),
  unirootTolFactor = 1e-06,
  ...
)
```

## Arguments

midp	logical. Use mid-p confidence distribution method? Currently only implemented where wmtype = "max"
nmc	Calculation method when midp = TRUE.
wmtype	type of modification for the Gamma confidence interval.

unirootTolFactor  
                                  tolerance factor for uniroot where midp = TRUE and nmc = 0.  
...                               Currently ignored.

**Value**

A list of arguments to pass to [wspoissonTest](#).

If midp = TRUE, with values

midp

nmc

unirootTolFactor

If midp = FALSE, with values:

wmtype

**See Also**

[wspoissonTest](#)

# Index

\* **datasets**

downs.mi, 5

\* **package**

dsrTest-package, 2

asymptoticControl, 3, 7, 8

betaControl, 4, 7, 8

dobsonControl, 5, 7, 8

downs.mi, 5

dsrTest, 6

dsrTest-package, 2

gammaControl, 4, 7, 8, 8

poisson.exact, 5, 7, 8

wspoissonTest, 3, 6–9